



Male Connector



Metric Range:ISO Tapered Thread

Part No.	Tube O. D. T mm	P * R(PT)	E Min	Width across flat		D	C	ℓ	L
				F mm	G mm				
PMC-M02-02	2	1/8	1.7	12	12	12.9	15.3	23.9	30.5
PMC-M03-02	3	1/8	2.4	12	12	12.9	15.3	23.1	29.7
PMC-M03-04	3	1/4	2.4	14	12	12.9	15.3	29.0	35.6
PMC-M04-02	4	1/8	2.4	12	12	13.7	16.1	24.6	31.2
PMC-M04-04	4	1/4	2.4	14	12	13.7	16.1	29.7	36.3
PMC-M06-02	6	1/8	4.8	14	14	15.3	17.7	25.4	32.8
PMC-M06-04	6	1/4	4.8	14	14	15.3	17.7	30.2	37.6
PMC-M06-06	6	3/8	4.8	17	14	15.3	17.7	31.0	38.4
PMC-M06-08	6	1/2	4.8	22	14	15.3	17.7	36.6	44.0
PMC-M08-02	8	1/8	4.8	15	16	16.2	18.6	26.7	34.2
PMC-M08-04	8	1/4	6.4	15	16	16.2	18.6	31.2	38.7
PMC-M08-06	8	3/8	6.4	17	16	16.2	18.6	31.7	39.2
PMC-M08-08	8	1/2	6.4	22	16	16.2	18.6	37.3	44.8
PMC-M10-02	10	1/8	4.8	18	19	17.2	19.5	28.7	36.3
PMC-M10-04	10	1/4	7.1	18	19	17.2	19.5	33.3	40.9
PMC-M10-06	10	3/8	7.9	18	19	17.2	19.5	33.3	40.9
PMC-M10-08	10	1/2	7.9	22	19	17.2	19.5	38.1	45.7
PMC-M12-04	12	1/4	7.1	22	22	22.8	22.0	33.3	43.4
PMC-M12-06	12	3/8	9.5	22	22	22.8	22.0	33.3	43.4
PMC-M12-08	12	1/2	9.5	22	22	22.8	22.0	38.1	48.2
PMC-M12-12	12	3/4	9.5	27	22	22.8	22.0	38.9	49.0
PMC-M15-08	15	1/2	11.9	24	25	24.4	22.0	38.9	49.0
PMC-M16-04	16	1/4	7.1	24	25	24.4	22.0	34.0	44.1
PMC-M16-06	16	3/8	9.5	24	25	24.4	22.0	34.0	44.1
PMC-M16-08	16	1/2	11.9	24	25	24.4	22.0	38.9	49.0
PMC-M16-12	16	3/4	12.7	27	25	24.4	22.0	38.9	49.0
PMC-M18-08	18	1/2	11.9	27	30	24.4	22.0	40.4	50.5
PMC-M18-12	18	3/4	15.1	27	30	24.4	22.0	40.4	50.5
PMC-M20-08	20	1/2	11.9	30	32	26.0	22.0	42.2	52.3
PMC-M20-12	20	3/4	15.9	30	32	26.0	22.0	42.2	52.3
PMC-M22-12	22	3/4	15.9	30	32	26.0	22.0	42.2	52.3
PMC-M22-16	22	1	18.3	35	32	26.0	22.0	47.8	57.9
PMC-M25-12	25	3/4	15.9	35	38	31.3	26.5	45.2	57.5
PMC-M25-16	25	1	21.8	35	38	31.3	26.5	50.0	62.3

All dimensions are in millimeters unless otherwise specified. Dimensions are for reference only, subject to change.